ARMSTRONG LINOLEUM

Lancaster, PA www.armstrong.com

CSI# 096516 Linoleum

Linoleum was invented 150 years ago, of linseed oil, cork and wood powder, resins and mineral pigments on a jute backing. Not to be confused with vinyl. Resilient flooring, available mostly in sheet form; less resistant to warping than tiles. Available in a wide range of saturated colors.

FINISHES



	CATEGORY	Rating	KEY POINTS
MATERIAL	Recycled/Renewable Content		35% pre-consumer recycled content, 36% renewable
	End of Life		Biodegradable
	Production Process		Ingredients mixed together, rolled between cylinders
PRODUCT USE	Installation		Professional installation, heat welded seams
	Longevity/Durability		40 years
	Maintenance		Easy to clean, needs to be polished to prevent stains
	Initial Cost		Less than market, contact dealer
	Resource Savings		
НЕАСТН	Installation Toxins		Low-VOC , naturally antibacterial
	Manufacturing Toxins		
Отнек	Product Notes		Does not trap dirt, moisture or debris; good for people
			with asthma
Notes	Company Profile	In 1985, the Armstrong Foundation was formed to enhance the neighborhoods in which its employees live and work. Millions of dollars each year have been donated to community caring efforts.	